













**Fiscal Suggestion** 3 inch Impact Dot **POS** Printer

**SRP-270** 



### HIGHLIGHTS

- •Match the model to your application with three impact printer models
- SRP-270A: Tear bar
- SRP-270C: Auto-cutter
- SRP-270D: Auto-cutter with spooler
- · High operational reliability (1.8 million lines MCBF)
- ·Reduce waiting time with its fast output printing 40 columns at 4.6 lines per second
- •SRP-270D type version automatically spools printed paper into a conveniently storable roll.
- · Produce flawless pre printed documents with its black mark
- Space efficient optional vertical and wall mount kits available.
- · Easy to install ribbon cartridge (Black / Black & Red)

The BIXOLON SRP-270 is a high quality and reliable impact dot POS printer (spooler option). The SRP-270 is an ideal printer for point of sale and hospitality applications. The modular user-friendly design, graphics capability, and 4.6 lps print speed offer reliable high performance in a compact, lightweight design. With the fast moving technology of today it is important to have simple integration of peripheral devices. The SRP-270 receipt printer is no exception; drivers are available for Windows and OPOS. Other features of the SRP-270 receipt printer include a paper end sensor that automatically alerts the user when the printer is out of paper, a tear-bar or auto-cutter, and the ability to print one original receipt plus two copies.

## **SPECIFICATIONS**

- PRINTING METHOD: 9 Pin Serial Dot Matrix
- PRINTING SPEED: 4.6 lps
- RESOLUTION: Horizontal Resolution: 80 dpi Vertical Resolution: 144 dpi
- CHARACTER SIZE (W X H dots): Font A: 9 x 9 / Font B: 7 x 9 Korean: 17 x 9 / Chinese: 16 x 16
- CHARACTERS PER LINE:

FontA: 33, Font B: 40

Korean: 20, Chinese: 22 (3half dot: 21)

• CHARACTER SET : Alphanumeric Character : 95 Extended Character: 128 x 7 pages International Character: 32

• WIDTH: 76 ± 0.5mm

• PAPER ROLL DIAMETER: Max Ø 83.0mm • PAPER LOADING: Easy Paper Loading

• PRINTER UNIT: 18 million lines • HEAD: 300 million dots / wire • AUTO CUTTER: 1 million cuts

INTERFACE: Serial(RS-232C / RS-485), Parallel (IEEE1284), USB

**EMULATION: BXL/POS DRIVER**: Windows, OPOS **SENSOR**: Paper End Sensor **DRAWER PORT**: 2 ports

POWER SUPPLY (SMPS): AC 100~240V / DC 24V, 1.5A

### **DIMENSIONS (WXLXHmm)** • SRP-270A: 160 x 249 x 130

• SRP-270C: 160 x 249 x 149 • SRP-270D: 160 x 295 x 160

**OPERATING TEMPERATURE:** 0~45°C/32~113°F

- RIBBON CARTRIDGE (RRC-201B/RRC-201BR)
- BIXOLON MELODIST (RMB-100)

# BIXOLON

BR-SRP-270-EN-MAR10-V1

Copyright @ BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

www.bixolon.com



BIXOLON Co..Ltd.

7-8th FL, Miraeasset Venture Tower, 685, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, KOREA (ROK)

+82 (0) 31 218 5500 +82 (0) 31 218 5589 E-mail sales@bixolon.com

BIXOLON America Inc. 3171 Fujita St Torrance, CA 90505, USA

+1 858 764 4580 +1 310 257 6869 E-mail sales@bixolonusa.com **BIXOLON Europe GmbH** Tiefenbroicher Weg 35, 40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0 +49 211 68 78 54 20 Fax E-mail sales@bixolon.de